





EDGE-LIT EXIT SIGNS

	ELECTRIC	AL CHARACTERISTICS	
Model #	Lamp Type	Sides	Background
RPEXITELD	LED - Red "Exit"	Double Sided	Mirrored
RPEXITELS	LED - Red "Exit"	Single Sided	Acrylic Clear
	PACKI	NG INFORMATION	
Model #	Units Per Carton	Weight Per Unit	Cube Unit
RPEXITELD	6 pc.	2.9 lbs.	0.17 cu.
RPEXITELS	6 pc.	2.9 lbs.	0.17 cu.

Construction & Application

- APPLICATION: Suitable for use in almost any commercial or light industrial application.
- APPROVALS: ETL listed.
- HOUSING: The housing is made of Aluminum. White trim Red or Green letters



- MOUNTING: Easy snap fit canopy can be used for top or end mounting or knockouts can be used for surface
 mounting. Included second face allows the unit to be used as a single or double face exit sign. Snap fitting,
 replaceable chevrons for direction indication.
- LAMPS: Long life Light Emitting Diode (LED) lamps provide the maximum in energy savings.
- ELECTRICAL / BATTERY: Dual voltage input 120/277 VAC, 60 Hz.
 Suitable for Damp Location



SINGLE FACE: CLEAR LENS · DOUBLE FACE: MIROOR LENS

ELECTRICAL CHARACTERISTICS				
Model #	Lamp Type	Sides	Background	
RPEXITELD-GRN	LED - Green "EXIT"	Double Sided	Mirrored	
RPEXITELD-GRN	LED - Green "EXIT"	Single Sided	Acrylic Clear	