



" V P "

SECURITY  
SERIES

PREMIUM  
SECURITY  
LIGHT

Excellent for lighting areas where vandal resistant applications such as schools, parks, jails, public bathrooms are a must.

s p e c i f i c a t i o n s

h o u s i n g	l e n s	o p t i o n s
---------------	---------	---------------

- Die formed heavy gauge steel
- Mounts on ceiling or wall

- Injection molded clear prismatic polycarbonate with UV inhibitors for minimum discoloration
- Integral locking lugs opposite screws for improved vandal resistance
- Diffuser may be attached with optional tamper proof screws
- Available in 4' lengths
- Lens completely encloses body to further inhibit vandalism

**BALLAST**

- EB Electronic T8
- M2 Magnetic T12

**VOLTAGE**

- 1 120V
- 7 277V
- U Universal 120 - 277V

**GENERAL OPTIONS**

- TP Tamper-proof screws
- EM Emergency Pack
- PC Polycarbonate Lens (Standard)

e l e c t r i c a l

- Neoprene gasketed enclosure
- 120 Volt Class "P" ballast is standard, consult ordering guide for additional options available
- All electrical components are U.L. listed

Consult Factory for lamp options or additional specification requirements not shown.

standard ordering information	option availability
-------------------------------	---------------------

MODEL#	LAMP TYPE	A B C			option availability							
		LENGTH	WIDTH	DEPTH	1	7	EB	M2	EM	TP	U	
VP254HO	F54T5HO	50 1/4"	8 1/4"	3 1/2"								•
VP240	F40T12	50 1/4"	8 1/4"	3 1/2"	STD	•		•	•	•		
VP232	F32T8	50 1/4"	8 1/4"	3 1/2"	STD	• •	STD		•	•		

• \*\*Consult Factory      STD Standard      • Available option

- U.L. listed for damp locations

